



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	06-7087-7	<b>Version number:</b>	5.00
<b>Issue Date:</b>	29/08/2016	<b>Supersedes date:</b>	19/08/2013

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### IDENTIFICATION:

#### 1.1. Product identifier

3M™ Rigid Parts Plastic Repair Adhesive, PN 05883, 05885, 55885

#### Product Identification Numbers

60-9800-3084-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Two-part epoxy type adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

**Company Emergency Hotline:** EMERGENCY: 1800 097 146 (Australia only)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

06-3176-2, 06-3177-0

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

### TRANSPORT INFORMATION

For transportation and storage this KIT and its components are NOT classified as Dangerous Goods

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge

at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	06-3177-0	<b>Version number:</b>	5.00
<b>Issue Date:</b>	28/08/2016	<b>Supersedes date:</b>	19/08/2013

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Use with Part A, MSDS 06-3176-2

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

#### Signal word

DANGER!

**Symbols**

Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

H317 May cause an allergic skin reaction.  
H350 May cause cancer.  
H372 Causes damage to organs through prolonged or repeated exposure:  
respiratory system |

**Precautionary statements**

**General:**

P102 Keep out of reach of children.  
P103 Read label before use.  
P101 If medical advice is needed, have product container or label at hand.

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280E Wear protective gloves.  
P281 Use personal protective equipment as required.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see Notes to Physician on this label).  
P314 Get medical advice/attention if you feel unwell.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

Causes mild skin irritation. Causes eye irritation. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

### SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Epichlorohydrin	106-89-8	< 0.01
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	25068-38-6	40 - 70
Talc	14807-96-6	10 - 30
Limestone	1317-65-3	10 - 30
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	74398-71-3	3 - 7
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	1 - 5
Quartz	14808-60-7	<= 0.25

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

##### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

##### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

##### Substance

Aldehydes.  
Carbon monoxide.  
Carbon dioxide.  
Toxic vapour, gas, particulate.

##### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

No special storage requirements.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Epichlorohydrin	106-89-8	ACGIH	TWA:0.5 ppm	A3: Confirmed animal carcin., SKIN
Epichlorohydrin	106-89-8	Australia OELs	TWA(8 hours):7.6 mg/m3(2 ppm)	SKIN
Limestone	1317-65-3	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Quartz	14808-60-7	Australia OELs	TWA(8 hours):0.1 mg/m3;Limit value not established:	
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association  
Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment  
CMRG : Chemical Manufacturer's Recommended Guidelines  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling  
Sen: Sensitiser  
Sk: Absorption through the skin may be a significant source of exposure.

## **8.2. Exposure controls**

### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### **8.2.2. Personal protective equipment (PPE)**

#### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

#### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Appearance/Odour</b>	Blue, with little odour.

Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	
Flash point	No flash point
Evaporation rate	No data available.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	No data available.
Vapour density	No data available.
Density	1 g/ml
Relative density	1 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
Viscosity	No data available.
Volatile organic compounds (VOC)	1 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0.1 % weight [Test Method:calculated per CARB title 2]
Percent volatile	No data available.
VOC less H2O & exempt solvents	1 g/l [Test Method:calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

**Substance**

**Condition**

None known.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.



## 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Additional Health Effects:

#### Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	Ingestion	Rat	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
Epichlorohydrin	Dermal	Rabbit	LD50 755 mg/kg
Epichlorohydrin	Inhalation-Vapour (4 hours)	Rat	LC50 1.7 mg/l
Epichlorohydrin	Ingestion	Rat	LD50 260 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Rabbit	Mild irritant
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Quartz	Professional judgement	No significant irritation
Epichlorohydrin	Human and animal	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Rabbit	Moderate irritant
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Epichlorohydrin	Rabbit	Corrosive

**Skin Sensitisation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Human and animal	Sensitising
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not sensitizing
Epichlorohydrin	Human and animal	Sensitising

**Respiratory Sensitisation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Human	Not sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	In vivo	Not mutagenic
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
Epichlorohydrin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epichlorohydrin	In vivo	Mutagenic

**Carcinogenicity**

Name	Route	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Quartz	Inhalation	Human and animal	Carcinogenic.
Epichlorohydrin	Dermal	Mouse	Not carcinogenic
Epichlorohydrin	Ingestion	Rat	Carcinogenic.
Epichlorohydrin	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation
Limestone	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	pre mating & during gestation
Talc	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Epichlorohydrin	Inhalation	Not toxic to female reproduction	Rat	NOAEL 0.2 mg/l	10 weeks
Epichlorohydrin	Inhalation	Not toxic to development	Multiple animal species	NOAEL 0.09 mg/l	during organogenesis

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

Epichlorohydrin	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 160 mg/kg/day	during gestation
Epichlorohydrin	Ingestion	Toxic to male reproduction	Rat	LOAEL 6.25 mg/kg/day	23 days
Epichlorohydrin	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.02 mg/l	10 weeks

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
Epichlorohydrin	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	occupational exposure
Epichlorohydrin	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
Limestone	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 18 mg/m3	113 weeks

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

			classification			
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Epichlorohydrin	Inhalation	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.21 mg/l	19 days
Epichlorohydrin	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.04 mg/l	136 weeks
Epichlorohydrin	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.377 mg/l	4 weeks
Epichlorohydrin	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.211 mg/l	4 weeks
Epichlorohydrin	Inhalation	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.02 mg/l	98 days
Epichlorohydrin	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.002 mg/l	98 days
Epichlorohydrin	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.02 mg/l	13 weeks
Epichlorohydrin	Inhalation	blood	All data are negative	Rat	NOAEL 0.189 mg/l	90 days
Epichlorohydrin	Ingestion	heart   blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 80 mg/kg/day	12 weeks
Epichlorohydrin	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 25 mg/kg/day	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7		Data not available or insufficient for classification			
Epichlorohydrin	106-89-8	Water flea	Experimental	48 hours	EC50	21 mg/l
Epichlorohydrin	106-89-8	Green Algae	Experimental	96 hours	IC50	16 mg/l
Epichlorohydrin	106-89-8	Fathead minnow	Experimental	96 hours	LC50	10.6 mg/l
Talc	14807-96-6		Data not available or insufficient for classification			
Quartz	14808-60-7		Data not available or insufficient for classification			
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	74398-71-3		Data not available or insufficient for classification			
Limestone	1317-65-3	Western Mosquitofish	Experimental	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Experimental	21 days	NOEC	>100 mg/l
4,4'-Isopropylidene	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

diphenol-Epichlorohydrin Polymer						
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	25068-38-6	Ricefish	Experimental	96 hours	LC50	1.41 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Epichlorohydrin	106-89-8	Experimental Hydrolysis		Hydrolytic half-life	8.2 days (t 1/2)	Other methods
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	25068-38-6	Laboratory Hydrolysis		Hydrolytic half-life	<2 days (t 1/2)	Other methods
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	74398-71-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Epichlorohydrin	106-89-8	Experimental Biodegradation	14 days	BOD	67.9 % weight	OECD 301C - MITI test (I)
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	25068-38-6	Laboratory Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Quartz	14808-60-7	Data not	N/A	N/A	N/A	N/A

**3M™ Rigid Parts Repair Adhesive, PN 05883, 05885, 08275,08266, 55885 Part B**

		available or insufficient for classification				
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2,3-Propanetriyl Ester of 12-(Oxiranylmethoxy)-9-Octadecenoic Acid	74398-71-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-Isopropylidene diphenol-Epichlorohydrin Polymer	25068-38-6	Laboratory BCF - Other	28 days	Bioaccumulation factor	<42	Other methods
Epichlorohydrin	106-89-8	Experimental Bioconcentration		Log Kow	0.45	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

**SECTION 14: Transport Information**

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: Not applicable.

Proper shipping name: Not applicable.



**Class/Division:** Not applicable.  
**Sub Risk:** Not applicable.  
**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable  
**IERG:** Not applicable.

**International Air Transport Association (IATA) - Air Transport**

**UN No.:** Not applicable.  
**Proper shipping name:** Not applicable.  
**Class/Division:** Not applicable.  
**Sub Risk:** Not applicable.  
**Packing Group:** Not applicable.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** Not applicable.  
**Proper shipping name:** Not applicable.  
**Class/Division:** Not applicable.  
**Sub Risk:** Not applicable.  
**Packing Group:** Not applicable.  
**Marine Pollutant:** Not applicable.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

**Revision information:**

Conversion to GHS format SDS.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	06-3176-2	<b>Version number:</b>	6.00
<b>Issue Date:</b>	29/08/2016	<b>Supersedes date:</b>	19/08/2013

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Rigid Parts Repair Adhesive Part A (Accelerator) PN 05883, 05885, 08275, 08266, 55885

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Use with Part B, MSDS 06-3177-0

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.  
Skin Corrosion/Irritation: Category 2.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 1A.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

DANGER!

**Symbols**

Corrosion | Health Hazard |

**Pictograms**



**Hazard statements**

H318	Causes serious eye damage.
H315	Causes skin irritation.
H361	Suspected of damaging fertility or the unborn child.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system

**Precautionary statements**

**General:**

P102	Keep out of reach of children.
P103	Read label before use.
P101	If medical advice is needed, have product container or label at hand.

**Prevention:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P281	Use personal protective equipment as required.
P270	Do not eat, drink or smoke when using this product.
P264	Wash thoroughly after handling.

**Response:**

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P310	Immediately call a POISON CENTRE or doctor/physician.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see Notes to Physician on this label).
P314	Get medical advice/attention if you feel unwell.

**Storage:**

P405	Store locked up.
------	------------------

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

### 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

May be harmful if swallowed.

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Mercaptan-Terminated Epoxy Curing Agent	Trade Secret	40 - 70
Talc	14807-96-6	10 - 30
Limestone	1317-65-3	10 - 30
Butyl Benzyl Phthalate	85-68-7	3 - 7
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	90-72-2	3 - 7
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	1 - 5
Quartz	14808-60-7	< 0.25

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide.  
Carbon dioxide.  
Oxides of nitrogen.  
Oxides of sulphur.  
Toxic vapour, gas, particulate.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Limestone	1317-65-3	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m3	
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.

**3M™ Rigid Parts Repair Adhesive Part A (Accelerator) PN 05883, 05885, 08275, 08266, 55885**

Quartz	14808-60-7	Australia OELs	TWA(8 hours):0.1 mg/m <sup>3</sup> ;Limit value not established:	
--------	------------	----------------	--	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene.

Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state

Solid. Paste

<b>Specific Physical Form:</b>	Paste
<b>Appearance/Odour</b>	Strong mercaptan odour.
<b>Odour threshold</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not classified
<b>Relative density</b>	1 [ <i>Ref Std: WATER=1</i> ]
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Volatile organic compounds (VOC)</b>	1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Volatile organic compounds (VOC)</b>	0.1 % weight [ <i>Test Method: calculated per CARB title 2</i> ]
<b>VOC less H2O &amp; exempt solvents</b>	1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Dermal	Rabbit	LD50 > 10,200 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	Rat	LD50 2,600 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Butyl Benzyl Phthalate	Dermal	Rabbit	LD50 > 10,000 mg/kg
Butyl Benzyl Phthalate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.7 mg/l
Butyl Benzyl Phthalate	Ingestion	Rat	LD50 2,330 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Ingestion	Rat	LD50 1,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate



**Skin Corrosion/Irritation**

Name	Species	Value
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Butyl Benzyl Phthalate	Rabbit	No significant irritation
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Quartz	Professional judgement	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Butyl Benzyl Phthalate	Rabbit	Mild irritant
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
Butyl Benzyl Phthalate	Human and animal	Not sensitizing
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Guinea pig	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not sensitizing

**Respiratory Sensitisation**

Name	Species	Value
Talc	Human	Not sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Butyl Benzyl Phthalate	In Vitro	Not mutagenic
Butyl Benzyl Phthalate	In vivo	Some positive data exist, but the data are not sufficient for classification
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	In Vitro	Not mutagenic
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Butyl Benzyl Phthalate	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Quartz	Inhalation	Human and animal	Carcinogenic.

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Limestone	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Talc	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Butyl Benzyl Phthalate	Ingestion	Toxic to female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
Butyl Benzyl Phthalate	Ingestion	Toxic to male reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
Butyl Benzyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	2 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
Butyl Benzyl Phthalate	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.789 mg/l	90 days

**3M™ Rigid Parts Repair Adhesive Part A (Accelerator) PN 05883, 05885, 08275, 08266, 55885**

Butyl Benzyl Phthalate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 240 mg/kg/day	2 years
Butyl Benzyl Phthalate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 960 mg/kg/day	90 days
Butyl Benzyl Phthalate	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg/day	2 years
Butyl Benzyl Phthalate	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 381 mg/kg/day	90 days
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Dermal	skin   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 125 mg/kg/day	28 days
Tris(2,4,6-Dimethylaminomonomethyl) Phenol	Dermal	auditory system   hematopoietic system   eyes	All data are negative	Rat	NOAEL 125 mg/kg/day	28 days
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

Acute aquatic hazard:

**3M™ Rigid Parts Repair Adhesive Part A (Accelerator) PN 05883, 05885, 08275, 08266, 55885**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Talc	14807-96-6		Data not available or insufficient for classification			
Quartz	14808-60-7		Data not available or insufficient for classification			
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7		Data not available or insufficient for classification			
Limestone	1317-65-3	Western Mosquitofish	Experimental	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Experimental	21 days	NOEC	>100 mg/l
Butyl Benzyl Phthalate	85-68-7	Mysid Shrimp	Experimental	96 hours	EC50	0.74 mg/l
Butyl Benzyl Phthalate	85-68-7	Rainbow trout	Experimental	96 hours	EC50	0.82 mg/l
Butyl Benzyl Phthalate	85-68-7	Green Algae	Experimental	72 hours	EC50	2.39 mg/l
Butyl Benzyl Phthalate	85-68-7	Fish	Experimental	96 hours	LC50	0.51 mg/l
Butyl Benzyl Phthalate	85-68-7	Mysid Shrimp	Experimental	28 days	NOEC	0.075 mg/l
Butyl Benzyl Phthalate	85-68-7	Fathead minnow	Experimental	30 days	NOEC	0.14 mg/l
Tris(2,4,6-Dimethylamino monomethyl) Phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	175 mg/l
Tris(2,4,6-Dimethylamino monomethyl) Phenol	90-72-2	Grass Shrimp	Experimental	96 hours	LC50	718 mg/l
Mercaptan-Terminated Epoxy Curing Agent	Trade Secret		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not available or insufficient for	N/A	N/A	N/A	N/A

**3M™ Rigid Parts Repair Adhesive Part A (Accelerator) PN 05883, 05885, 08275, 08266, 55885**

		classification				
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mercaptan-Terminated Epoxy Curing Agent	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tris(2,4,6-Dimethylamino monomethyl) Phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test
Butyl Benzyl Phthalate	85-68-7	Experimental Biodegradation	28 days	CO2 evolution	93 % weight	OECD 301B - Modified sturm or CO2

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mercaptan-Terminated Epoxy Curing Agent	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Butyl Benzyl Phthalate	85-68-7	Experimental BCF - Bluegill	21 days	Bioaccumulation factor	663	Other methods
Tris(2,4,6-Dimethylamino monomethyl) Phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	Other methods

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

### SECTION 14: Transport Information

#### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

#### International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

#### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

**Revision information:**

Conversion to GHS format SDS.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**