

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 1- 8

## 1. Identification of the substance/mixture and of the company/undertaking

**Product name** PERMAHYD  
BEISPRITZ-ADDITIV 1050

**Product code** 4025331463436

**Recommended use of the chemical**

Coating for professional use

**Restrictions on use**

The product is only for industrial and/or professional use, not for any private consumer use.

**Information on the Manufacturer/Supplier/Distributor**

Producer/Supplier Axalta Coating Systems Australia Pty Limited  
Street/Box 15 - 23 Melbourne Road, Riverstone NSW 2765, Australia

**Product Information**

Telephone +61 (0)2 8818 4300  
<http://www.spieshecker.com.au>

**Emergency Information**

Emergency telephone number 1800 089 766  
AU Poisons Information Centre: 131 126  
Transportation Emergency Phone 1800 089 766

## 2. Hazards identification

Classified as HAZARDOUS according to the GHS criteria under Australian Work Health Safety (WHS) Act 2011.  
Not classified as dangerous goods according to the Australian Dangerous Goods (ADG) Code.

**GHS-Classification**

Flammable liquids Category 4  
Serious eye damage/eye irritation Category 1

**GHS-Labeling**

Hazard symbols



Signal word: Danger

Hazard statements

Combustible liquid.  
Causes serious eye damage.

Precautionary statements

Keep away from open flames/hot surfaces. - No smoking.  
Wear eye protection/ face protection.  
Wear protective gloves/ eye protection/ face protection.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER/doctor.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local regulations.

**Other hazards which do not result in classification**

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 2- 8

None known.

**Special hazard instructions for humans and environment**

Do not breathe vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment.  
Restricted to professional users.

### 3. Composition/information on ingredients

**Chemical nature**

Mixture of synthetic resins and solvents as well as water

**Hazardous components**

CAS-No.	Chemical name	Concentration	GHS Hazardous
71-41-0	pentan-1-ol	3 - 5%	√

Non-regulated ingredients 90 - 100%

### 4. First aid measures

**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

**Skin contact**

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Inhalation**

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Ingestion**

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

**Most Important Symptoms/effects, acute and delayed****Inhalation**

May cause nose and throat irritation. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

**Ingestion**

May result in gastrointestinal distress.

**Skin or eye contact**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

**Indication of immediate medical attention and special treatment needed if necessary**

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

### 5. Firefighting measures

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 3- 8

## Suitable extinguishing media

Water spray, Dry chemical, Foam

## Extinguishing media which shall not be used for safety reasons

High volume water jet

## Hazardous combustion products

CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

## Fire and Explosion Hazards

Avoid heating above flash point.

## Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## Additional information

Hazchem Code:

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

### Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

### Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

### Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

For personal protection see section 8. Comply with the health and safety at work laws. If material is a coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

### Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

### Storage

#### Requirements for storage areas and containers

Storage temperature: +5 to +35°C. Observe label precautions. Storage temperature: +5 to +35°C. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

## 8. Exposure controls/personal protection

### Additional technical information on the plant

# SAFETY DATA SHEET



Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 4- 8

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. During spray operations, use spray booth fitted to airflow requirements of AS/NZS 4114.

## National occupational exposure limits

CAS-No.	Chemical name	Values	Control Parameters	Basis
71-41-0	pentan-1-ol			no exposure standard allocated

## Glossary

STEL Short term exposure limit

TWA Time weighted average

## Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

## Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical name	Glove material	Glove thickness	Break through time
	Nitrile rubber	0.33 mm	60 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

## Eye protection

Use safety eyewear designed to protect against splash of products.

## Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

## Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

## Environmental exposure controls

Do not let product enter drains.

For ecological information refer to section 12.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

#### Appearance

**Form:** liquid; **Colour:** milky; **Odour:** Odour is not perceptible.; **Odor Threshold :** No data available

#### Important health, safety and environmental information

Property	Value	Method
pH	7.8 – 8.2	
Melting point/freezing point	NIL	
Boiling point/boiling range	100 °C	
Flash point	69 °C	EN ISO 3679 Does not sustain combustion.

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 5- 8

Evaporation rate	Slower than Ether	
Flammability (solid, gas)	not relevant as product is liquid	
Lower explosion limit	No data available	
Upper explosion limit	No data available	
Vapour pressure	2.4 hPa	
Vapour density	No data available	
Density	1.01 g/cm <sup>3</sup>	20 °C - DIN 53217/ISO 2811
Solubility(ies)		
Water solubility	appreciable	
Solubility in other solvents	No data available	
Partition coefficient: n-octanol/water	This product is a mixture. For ingredient details see section 12	
Auto-ignition temperature	300 °C	DIN 51794 based on organic solvent content
Decomposition temperature	This product is a mixture. For further information see section 10.	
Viscosity (23 °C)	<20 s	ISO 2431 - 1993 6 mm
Explosive properties	Not explosive	
Oxidizing properties	not oxidizing	

### Other data

Solvent separation test	< 3%	ADR/RID
Content of volatile components (including water)	82.9 %	Basis Vapour pressure >= 0.01 kPa
organic solvent content	5.6 %	Basis Vapour pressure >= 0.01 kPa

## 10. Stability and reactivity

### Stability

Stable

### Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

### Hazardous Polymerization

Will not occur.

### Sensitivity to Static Discharge

If heated above the flash point, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

### Sensitivity to Mechanical Impact

None known.

## 11. Toxicological information

### Information on likely routes of exposure

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 6- 8

**Inhalation**

May cause nose and throat irritation. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

**Ingestion**

May result in gastrointestinal distress.

**Skin or eye contact**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

**Delayed and immediate effects and also chronic effects from short and long term exposure:****Acute oral toxicity**

not hazardous

**Acute dermal toxicity**

not hazardous

**Acute inhalation toxicity**

not hazardous

% of unknown composition: 0 %

**Skin corrosion/irritation**

Not classified according to GHS criteria

**Serious eye damage/eye irritation**

pentan-1-ol Category 1

**Respiratory sensitisation**

Not classified according to GHS criteria

**Skin sensitisation**

Not classified according to GHS criteria

**Germ cell mutagenicity**

Not classified according to GHS criteria

**Carcinogenicity**

Not classified according to GHS criteria

**Toxicity for reproduction**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Single exposure**

Not classified according to GHS criteria

**Target Organ Systemic Toxicant - Repeated exposure**

Not classified according to GHS criteria

**Aspiration toxicity**

Not classified according to GHS criteria

**Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )**

No information available.

**Symptoms related to the physical, chemical and toxicological characteristics**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 7- 8

of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## 12. Ecological information

### Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. The data in this section is consistent with data from chemical safety reports available at the date of revision.

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in soil

No information available.

### Other adverse effects

No information available.

## 13. Disposal considerations

Incinerate or otherwise dispose of waste material in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not incinerate in closed containers.

### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. If recycling is not practicable, dispose of in compliance with local regulations.

## 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

### Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

## 15. Regulatory information

### Symbol and indication of hazard.

Xi	Irritant
Contains	pentan-1-ol 3 - 5%.

### R-phrases(s)

R36	Irritating to eyes.
-----	---------------------

### S-phrases(s)

S23	Do not breathe vapour/spray.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.

Product name: PERMAHYD BEISPRITZ-ADDITIV 1050

Product code: 4025331463436

Print Date: 2018-09-07

v8.3

Last Revision Date: 2018-09-07

AU/en Page 8- 8

## National regulatory information

- Standard for the Uniform Scheduling of Medicines and Poisons
  - No poison schedule number allocated.
- Information about Other Regulations.
  - Not applicable

Restricted to professional users.

## 16. Other information

Sources of key data used to compile the datasheet

1. Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals, December 2011
2. Guidance on the Classification of Hazardous Chemicals Under The WHS Regulations, April 2012
3. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment
4. Australian Dangerous Goods Code, 7.3 (National Road Transport Commission)
5. Standard for the Uniform Schedule of Medicines and Poisons (SUSMP), No. 9
6. Labelling of Workplace Hazardous Chemicals Code of Practice, March 2015

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This Safety Data Sheet is valid in Australia for up to 5 years from listed Revision Date or when superseded by a later version.

### Report version

Version Changes

8.3 9

Last Revision Date: 2018-09-07

B12700779

End of Safety Data Sheet