

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem Bumper Structurant Spray
Product code : 142.982

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paints
Recommended restrictions : professional use, Industrial use on use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de
Telephone : 04122 717 0
Telefax : 04122 717158
Responsible Department : Laboratory
04122 717 0
sds@vosschemie.de

1.4 Emergency telephone number

Telephone : POISONS INFORMATION CENTRE
Australia
13 11 26

1.5 Details of the supplier/importer

Company : Sydney Automotive Paints and Equipment
Unit A3, 366 Edgar Street
Condell Park, 2200
reception@sape.com.au
Telephone : 02 9772 9000
Telefax : 02 9772 9001
Responsible Department : Marketing
02 9772 9000

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version

1.2

GB / EN

Revision Date:

26.07.2021

Date of last issue: 07.04.2021

Date of first issue: 07.10.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements

: EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

Precautionary statements

: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version
1.2

GB / EN

Revision Date:
26.07.2021

Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

ethyl acetate
n-butyl acetate
butanone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : aerosol
Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 50
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 2.5
---------	--	--	--------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : First aider needs to protect himself.
Remove from exposure, lie down.
If unconscious, place in recovery position and seek medical advice.
Take off contaminated clothing and shoes immediately.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Swallowing is not regarded as a possible method for exposure.
Immediately give large quantities of water to drink.
Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Hazchem: 2YE

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

media

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Vapours may form explosive mixtures with air.
Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment. Wear suitable respiratory protection equipment.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use water spray to cool unopened containers.
In the event of fire and/or explosion do not breathe fumes.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid inhalation of vapour or mist.
Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

- Environmental precautions : Should not be released into the environment.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Ventilate the area.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Local/Total ventilation : Ensure adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

- Advice on safe handling : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C / 122 °F. Also after use, do not open with force or burn.
Provide sufficient air exchange and/or exhaust in work rooms.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight.
- Hygiene measures : Do not inhale aerosol.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Please observe the storage instructions for aerosols! Keep containers tightly closed in a cool, well-ventilated place. Solvent vapours are heavier than air and may spread along floors. Keep away from direct sunlight. Keep away from heat and sources of ignition.
- Further information on storage conditions : Storage must be in accordance with the BetrSichV (Germany).
- Advice on common storage : Keep away from food and drink.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethyl acetate	141-78-6	STEL	400 ppm 1,468 mg/m ³	2017/164/EU
		Further information: Indicative		
		TWA	200 ppm 734 mg/m ³	2017/164/EU
		Further information: Indicative		
		TWA	200 ppm 734 mg/m ³	GB EH40
		STEL	400 ppm 1,468 mg/m ³	GB EH40
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
		Further information: Indicative		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version
1.2

GB / EN

Revision Date:
26.07.2021

Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
butane (containing < 0,1 % butadiene (203-450-8))	106-97-8	STEL	750 ppm 1,810 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA	600 ppm 1,450 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
butanone	78-93-3	TWA	200 ppm 600 mg/m ³	2000/39/EC
	Further information: Indicative			
		STEL	300 ppm 900 mg/m ³	2000/39/EC
	Further information: Indicative			
		TWA	200 ppm 600 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	300 ppm 899 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butanone	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	734 mg/m ³ 200 ppm
	Workers	Inhalation	Acute systemic effects, Acute local effects	1468 mg/m ³ 400 ppm
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local	734 mg/m ³ 200 ppm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version
1.2

GB / EN

Revision Date:
26.07.2021

Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

			effects	
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg
	Consumers	Ingestion	Long-term exposure	4.5 mg/kg
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
	Consumers	Inhalation	Long-term systemic effects	106 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	412 mg/kg
	Consumers	Oral	Long-term systemic effects	31 mg/kg
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
	Workers	Skin contact	Long-term systemic effects	343 mg/kg
	Consumers	Inhalation	Long-term systemic effects	114 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg
	Consumers	Oral	Long-term systemic effects	87 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Intermittent use/release	1.65 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
n-butyl acetate	Oral (Secondary Poisoning)	200 mg/kg
	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Soil	0.09 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version
1.2

GB / EN

Revision Date:
26.07.2021

Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

		weight (d.w.)
butanone	Fresh water	55.8 mg/l
	Marine water	55.8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284.74 mg/kg
	Marine sediment	284.7 mg/kg
	Soil	22.5 mg/kg
ethanol	Fresh water	0.96 mg/l
	Marine water	0.79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	3.6 mg/kg
	Marine sediment	2.9 mg/kg
	Soil	0.63 mg/kg
	Oral (Secondary Poisoning)	0.38 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Tightly fitting safety goggles
Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : >= 0.4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : No personal respiratory protective equipment normally required.
In case of inadequate ventilation wear respiratory protection.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Filter type : Filter type A-P

Protective measures : Use only with adequate ventilation.
When using do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Do not breathe vapours or spray mist.

Environmental exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2	26.07.2021	Date of first issue: 07.10.2019

Soil	:	Avoid subsoil penetration.
Water	:	Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	black
Odour	:	solvent-like
Melting point/freezing point	:	not determined
Initial boiling point and boiling range	:	Not applicable
Upper explosion limit / Upper flammability limit	:	11.5 %(V)
Lower explosion limit / Lower flammability limit	:	1.7 %(V)
Flash point	:	Not applicable
Ignition temperature	:	365 °C
pH	:	not determined substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	not determined
Vapour pressure	:	3,500 hPa (20 °C)
Density	:	0.79 g/cm ³ (20 °C)

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapour-air mixture.
Self-ignition	:	not auto-flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2 GB / EN	26.07.2021	Date of first issue: 07.10.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC0 (Rat): 22.5 mg/l, > 6000 ppm
Exposure time: 6 h
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10,760 mg/kg

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

butanone:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2 GB / EN	26.07.2021	Date of first issue: 07.10.2019

Acute oral toxicity : LD50 Oral (Rat): 3,460 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,000 mg/kg
Method: OECD Test Guideline 402

ethanol:

Acute oral toxicity : LD50 Oral (Rat): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 117 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

ethanol:

Result : Mild eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 610 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 650 mg/l
Exposure time: 16 h

Toxicity to fish (Chronic toxicity) : NOEC: > 75.6 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2.4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,972 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

ethanol:

Toxicity to fish : LC50 (Fish): 11,200 mg/l
Exposure time: 96 h
This product has no known ecotoxicological effects.

Toxicity to fish (Chronic toxicity) : NOEC: 250 mg/l
Species: Fish

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0.68 (25 °C)

butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)
pH: 7

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2 GB / EN	26.07.2021	Date of first issue: 07.10.2019

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Dispose of in conjunction with appropriate waste disposal authorities and in accordance with disposal regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
15 01 10, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version 1.2 GB / EN Revision Date: 26.07.2021 Date of last issue: 07.04.2021
Date of first issue: 07.10.2019

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

14.5 Environmental hazards

Hazchem: 2YE

ADN
Environmentally hazardous : no

ADR
Environmentally hazardous : no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2 GB / EN	26.07.2021	Date of first issue: 07.10.2019

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 840 g/l
VOC content for the product in a ready to use condition.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
EUH066	: Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version	Revision Date:	Date of last issue: 07.04.2021
1.2 GB / EN	26.07.2021	Date of first issue: 07.10.2019

Full text of other abbreviations

Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Bumper Structurant Spray

Version		Revision Date:	Date of last issue: 07.04.2021
1.2	GB / EN	26.07.2021	Date of first issue: 07.10.2019

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.