

Page 1/12

Printing date: 14.03.2022 Revision date: 24.01.2020

Version no. 1

Hazardous according to criteria of Australian Safety and Compensation Council.

# 1 Identification

- · Product identifier
- Trade name: BODY BLEND IN 777
- Article number: 847
- Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- · Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

HB BODY S.A. B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022. SINDOS THESSALONIKI.GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

#### Further information obtainable from:

Sydney Automotive Paints & Equipment PTY LTD Unit A3, 366 Edgar St. Condell Park NSW 2200 AUSTRALIA, Tel. +02 9772 9000, +02 9772 9001

# Emergency telephone number:

If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zeland 0800 764 766.

Safety Data Sheet

according to WHS Regulations

Page 2/12 Safety Data Sheet Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020 Version no. 1

Trade name: **BODY BLEND IN 777** 

# 2 Hazard(s) Identification

Classification of the substance or mixture



Flam. Lig. 3 H226 Flammable liquid and vapour.



health hazard

H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- Hazard-determining components of labelling:

toluene

#### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray. P260

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other hazards

### Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

Safety Data Sheet according to WHS Regulations

40-<45%

Page 3/12 Printing date: 14.03.2022 Revision date: 24.01.2020

Version no. 1

# Trade name: **BODY BLEND IN 777**

# 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of hazardous substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Index number: 607-195-00-7

CAS: 123-86-4 n-butyl acetate 40-<45%

EINECS: 204-658-1 Flam. Liq. 3, H226 Index number: 607-025-00-1 STOT SE 3, H336

RTECS: AF 7350000

CAS: 108-88-3 toluene 20-<25%

Index number: 601-021-00-3 🗞 Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304

RTECS: XS 5250000 Skin Irrit. 2, H315

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed Gastric or intestinal disorders
- Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours.

If blue colouring appears (lips, ear-lobes, finger-nails), give oxygen treatment as quickly as possible.

# 5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- · Speial protective equipment and fire fighting procedures: Mouth respiratory protective device.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Safety Data Sheet according to WHS Regulations

Page 4/12 Printing date: 14.03.2022 Revision date: 24.01.2020

Version no. 1

# Trade name: **BODY BLEND IN 777**

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and Storage

· Handling:

### Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

### Ingredients with limit values that require monitoring at the workplace:

#### 108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

#### 123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm

#### 108-88-3 toluene

WES Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Safety Data Sheet according to WHS Regulations

Page 5/12 Printing date: 14.03.2022 Revision date: 24.01.2020

Version no. 1

# Trade name: **BODY BLEND IN 777**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

### Respiratory protection:

Fresh air mask

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures. Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- Eye protection:



Body protection: Protective work clothing

# 9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid

**Colour:** According to product specification

Odour: CharacteristicOdour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/freezing point:
Initial boiling point and boiling range:

\*Flash point:

Undetermined.

110-111 °C

23 - 60 °C

Page 6/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020 Version no. 1

# Trade name: **BODY BLEND IN 777**

· Flammability (solid, gas): Not applicable.

· Autoignition temperature: 315 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:

Lower: 1.2 Vol %
Upper: 10.8 Vol %

'Vapour pressure at 20 °C: 29 hPa

Density at 20 °C: 0.91272 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

Solvent content:

 Organic solvents:
 100.0 %

 VOC (EC)
 912.7 g/l

 Solids content (volume):
 0.0 %

Other information No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological Information

- · Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

#### ATE (Acute Toxicity Estimates)

Oral LD50 25,000 mg/kg (rat) Inhalative LC50/4 h >33.1 mg/l (rat)

Safety Data Sheet according to WHS Regulations

Page 7/12 Printing date: 14.03.2022 Revision date: 24.01.2020

Version no. 1

# Trade name: **BODY BLEND IN 777**

# 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

# 123-86-4 n-butyl acetate

Oral LD50 13.100 ma/ka (rat) Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

#### 108-88-3 toluene

Oral LD50 5,000 mg/kg (rat) Dermal LD50 (static) 12,124 mg/kg (rabbit) 5,320 mg/l (mouse) Inhalative LC50/4 h

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eye damage/irritation No irritating effect.
- **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 1A

### 12 Ecological Information

- · Toxicity
- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- · Other adverse effects No further relevant information available.

ΔΠ

Page 8/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020 Version no. 1

# Trade name: **BODY BLEND IN 777**

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

# 14 Transport information

· UN-Number

ADG, IMDG, IATA UN1263

· UN proper shipping name

· **ADG** UN1263 PAINT

· IMDG, IATA PAINT

Transport hazard class(es)

· ADG



· Class 3 (F1) Flammable liquids.

· Label 3

IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· Packing group

· ADG, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30
 EMS Number: F-E,S-E
 Stowage Category A

· Transport in bulk according to Annex II of Marpol and

the IBC Code Not applicable.

· Transport/Additional information:

ADG

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3

Tunnel restriction code D/E

Page 9/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020

Version no. 1

# Trade name: **BODY BLEND IN 777**

· IMDG

Limited quantities (LQ) 5L
Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1263 PAINT, 3, III

· UN "Model Regulation":

# 15 Regulatory information

•3Y

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

Australian Inventory of Industrial Chemicals

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

108-88-3 toluene: S6

Australia: Priority Existing Chemicals

None of the ingredients is listed.

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms







GHS02

GHS07

· Signal word Danger

### Hazard-determining components of labelling:

toluene

#### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

Page 10/12 Safety Data Sheet Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020 Version no. 1

# Trade name: **BODY BLEND IN 777**

#### 16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

# · Department issuing SDS: Department of Quality Control

#### · Contact:

HB BODY S.A

Ms Olympia Stamkou Ph: +30 2310 790 032 fax: +30 2310 790 033

email: stamkou@hbbody.com

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Lig. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

### \* Data compared to the previous version altered.

Continue on page 11

Page 11/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 24.01.2020 Version no. 1

# Trade name: **BODY BLEND IN 777**

# Annex: Exposure scenario

- · Short title of the exposure scenario
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use According to directions for use.
- · Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

#### Technical protective measures

No special measures required.

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

### Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

### Environmental protection measures

- · Water Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
- · **Soil** The product is only processed over the concrete collecting basin.
- · Disposal measures Ensure that waste is collected and contained.

Page 12/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Version no. 1

Revision date: 24.01.2020

# Trade name: **BODY BLEND IN 777**

- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- \* Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- **Consumer** This product is to be used by professional technitians only.
- · Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

ΑU