

Page 1/12

Printing date: 14.03.2022 Revision date: 22.01.2020

Version no. 1

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

Trade name: BODY 960 ACTIVATOR

- · Article number: 782
- · Relevant identified uses of the substance or mixture and uses advised against Coating
- · Life cycle stages F Formulation or re-packing
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Technical function Corrosion inhibitor
- Application of the substance / the mixture

Activator

Surface protection

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbodv.com

email: hbbody@hbbody.com

Further information obtainable from:

Sydney Automotive Paints & Equipment PTY LTD Unit A3, 366 Edgar St. Condell Park NSW 2200 AUSTRALIA, Tel. +02 9772 9000, +02 9772 9001

Safety Data Sheet

according to WHS Regulations

Page 2/12 Safety Data Sheet Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020 Version no. 1

Trade name: **BODY 960 ACTIVATOR**

Emergency telephone number:

If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zeland 0800 764 766.

2 Hazard(s) Identification

Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irritation 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- Description: Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 3

Page 3/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020 Version no. 1

Trade name: **BODY 960 ACTIVATOR**

Dangerous components:

CAS: 67-63-0 propan-2-ol 80-<90%

Index number: 603-117-00-0 (*) Eye Irritation 2A, H319; STOT SE 3, H336

RTECS: NT 8050000

CAS: 7664-38-2 phosphoric acid 5-<10%

Index number: 015-011-00-6

RTECS: TB 6300000

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contanct lenses in case of eye contamination and irrigae copiously with clean water for at least 15 minutes trying to hold the eye lids open.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- * Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- · Speial protective equipment and fire fighting procedures: No special measures required.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

Page 4/12 Printing date: 14.03.2022 Revision date: 22.01.2020

Version no. 1

Trade name: **BODY 960 ACTIVATOR**

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WES Short-term value: 1230 mg/m³, 500 ppm Long-term value: 983 mg/m³, 400 ppm

7664-38-2 phosphoric acid

WES Short-term value: 3 mg/m³ Long-term value: 1 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Safety Data Sheet according to WHS Regulations

Page 5/12 Printing date: 14.03.2022 Revision date: 22.01.2020

Version no. 1

Trade name: **BODY 960 ACTIVATOR**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and Chemical Properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid

Colour: According to product specification

• Odour: Characteristic
• Odour threshold: Not determined.
• pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: $82 \,^{\circ}\text{C}$ Flash point: $< 23 \,^{\circ}\text{C}$

· Flammability (solid, gas): Not applicable.

· Autoignition temperature: 425 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:

Lower: 2 Vol %
Upper: 12 Vol %

'Vapour pressure at 20 °C: 43 hPa

Density at 20 °C:
Relative density

Vapour density

0.86765 g/cm³

Not determined.

Not determined.

Page 6/12 Safety Data Sheet Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020

Version no. 1

Trade name: **BODY 960 ACTIVATOR**

Evaporation rate Not determined.

Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

Solvent content:

Organic solvents: 87.4 % Water: 6.3 % VOC (EC) $802.1 \, g/l$ Solids content (volume): 6.3 %

 Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- *Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 34.3 mg/l (rat)

67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat) Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitising effect through inhalation is possible by prolonged exposure.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Safety Data Sheet Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020 Version no. 1

Page 7/12

Trade name: **BODY 960 ACTIVATOR**

12 Ecological Information

- · Toxicity
- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- * Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · UN-Number
- ADG, IMDG, IATA
- · UN proper shipping name
- · ADG
- IMDG, IATA
- · Transport hazard class(es)
- ADG



· Class 3 (F1) Flammable liquids.

UN1263

UN1263 PAINT RELATED MATERIAL, special provision 640D PAINT RELATED MATERIAL

Continue on page 8

Page 8/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020 Version no. 1

Trade name: **BODY 960 ACTIVATOR**

· Label 3

IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

Packing group

ADG, IMDG, IATA

· Environmental hazards:

Marine pollutant:

· Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33
 EMS Number: F-E,S-E
 Stowage Category B

· Transport in bulk according to Annex II of Marpol and

the IBC Code Not applicable.

· Transport/Additional information:

ADG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Transport category 2
Tunnel restriction code D/E

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

•3YE

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

7664-38-2 phosphoric acid: S5, S6

Australia: Priority Existing Chemicals

None of the ingredients is listed.

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Continue on page 9

Safety Data Sheet according to WHS Regulations

Printing date: 14.03.2022 Revision date: 22.01.2020

Version no. 1

Page 9/12

Trade name: **BODY 960 ACTIVATOR**

· Hazard pictograms





GHS02

P405

12 GHS

· Signal word Danger

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.
Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Department of Quality Control

· Contact:

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

Page 10/12

Printing date: 14.03.2022 Revision date: 22.01.2020

Version no. 1

Trade name: **BODY 960 ACTIVATOR**

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

AU Continue on page 11

Safety Data Sheet

according to WHS Regulations

Page 11/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020

Version no. 1

Trade name: **BODY 960 ACTIVATOR**

Annex: Exposure scenario

- · Short title of the exposure scenario
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9b Fillers, putties, plasters, modelling clay
- **Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- Technical function Corrosion inhibitor
- Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use According to directions for use.
- · Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

- · Water Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
- **Soil** The product is only processed over the concrete collecting basin.
- · Disposal measures Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- **Consumer** This product is to be used by professional technitians only.

Page 12/12 Safety Data Sheet
Printing date: 14.03.2022 according to WHS Regulations

Revision date: 22.01.2020 Version no. 1

Trade name: **BODY 960 ACTIVATOR**

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

ΑU